

# REVIVAL

HARDWOOD FLOORING



Specifications

# REVIVAL

HARDWOOD FLOORING

## Specifications

### Description:

Engineered European Oak hardwood flooring available in 8 color treatments.

### Available Sizes:

There are three available patterns and they produced in metric measurements.

Plank - 14mm thick x 180mm wide x 600-2150mm long  
[.55" thick x 7.08" wide x 23.62"-84.65" long]

5" Herringbone - 14mm thick x 127mm wide x 762mm long  
[.55" thick x 5" wide x 30" long]

7" Herringbone - 14mm thick x 180mm wide x 900mm long  
[.55" thick x 7.08" wide x 35.43" long]

### Wood Source:

European Oak [Botanical Name: Quercus SSP]

### Origin:

Germany and France

### Janka hardness:

1360

### Grade:

Plank - Rustic

Herringbone - Light Rustic

### Construction/Platform:

3 ply construction, 14mm [9/16"] overall

- 3mm lamella

- 9mm lumber core

- 2mm back

**Surface:**

Wire brushed texture

**Connection:**

Tongue and groove on sides and end matched

**Edge Treatment:**

Gently Chiseled Edges

**Finish:**

Commercial grade, UV cured, low VOC oil finish

**Installation Methods:**

Glue down, Nail down or stapled

**Radiant Heating:**

Only for use with water radiant heating systems,  
max 81° Fahrenheit surface temperature

**Green Attributes:**

CARB [California Air Resource Board] exempt. It meets regulations of the provision of California Code of Regulation 93120 concerning airborne toxic control measure to reduce the formaldehyde emission from composite wood product such as a lumber core or backer.

Our flooring is finished in a low VOC oil finish, free from solvent emissions and formaldehyde.

**Residential Warranty:**

25 year Structural and 25 year Finish